Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S1	7920	(717/116 or 707/102 or 707/103)".clss"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 13:26
S2	671	S1 and ((class$2 near5 (parent or child)) or superclass$2 or sub?class$2)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 13:29
S3	203	S2 and ((add$3 or new or defin$3 or declar$3) with (attribute$1 or variable$1 or field$1 or propert$3) with instance$1)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 14:11
S4	114	S3 and ((attribute$1 or variable$1 or field$1 or propert$3 or instance$1) with database$1)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 13:32
S5	90	S4 and (relational near3 database$1)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 13:32
S6	87	S5 and (table$1 and (attribute$1 or instance$1 or variable$1 or field$1 or propert$3))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 14:10
S7	32	S6 and (hash with table$1)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 13:35
S8	1	S7 and ((hash with table$1) with class$2 with (instance$1 or object$1))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 13:35
S9	1	S2 and (((child adj2 class$2) or sub?class$2) with (new near3 (attribute$1 or variable$1 or field$1 or propert$3 or member$1)))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 14:25
S10	9	S1 and ((different adj2 instances) with (different adj2 (attribute$1 or field$1 or variable$1 or propert$3 or member$1)))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/26 14:28

S11	7929	(717/116 or 707/102 or 707/103)".clss"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/31 12:18
S12	186	(class$2 with (instance$1 or object$1)) same ((stor$3 or sav$3 or record$3 or writ$3) with (object$1 or instance$1) with (relational adj2 database$1))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/31 13:15
S13	69	S11 and S12	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/31 13:14
S14	31	(class$2 with (instance$1 or object$1)) same ((hash adj2 table$1) with (variable$1 or member$1 or attribute$1 or propert$3))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/31 15:49
S15	19	(class$2 with (instance$1 or object$1)) same ((hash adj2 table$1) with (variables or members or attributes or properties))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/31 15:51
S16	12	(class$2 with (instance$1 or object$1) with (hash adj2 table$1)) same ((hash adj2 table$1) with (variables or members or attributes or properties))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/01/31 15:52